

Nevastane Silicone Spray



Aerosol – Food & Beverages Industry



Multipurpose, NSF-H1-certified Silicone Oil, suitable for incidental food contact

APPLICATIONS

- **NEVASTANE SILICONE SPRAY** contains a high viscosity silicone oil with excellent stability to provide maximum lubrication.
- **NEVASTANE SILICONE SPRAY** is multipurpose, with a wide operating temperature range (-60°C to +230°C): small machines and chains subject to extreme temperatures, shrink oven chains, conveyors, rails, joints, hinges, locks...
- **NEVASTANE SILICONE SPRAY** is recommended for the lubrication of numerous applications in food processing industries.
- **NEVASTANE SILICONE SPRAY** can also be used as a demolding agent.
- *Shake the aerosol before use – Spray from a 15-25 cm distance*

ADVANTAGES

- **NEVASTANE SILICONE SPRAY** is recommended for use where incidental contact with food may occur. Using maintenance lubricants which have been registered H1 with NSF minimizes your critical control points as required by HACCP.
- Anti-adhesive, anti-static, dielectric, water repellent.
- Anti-rust, anti-corrosion & very good insulation properties ; Without effect on metals and plastics.
- Does not dry, resists to shear and wet atmospheres.
- Non-flammable propellant gas : CO₂
- Can be used upside-down for an easier manipulation of the spray.

TYPICAL CHARACTERISTICS	METHODS	UNITS	TOTAL NEVASTANE Silicone Spray
Aspect	Visual	-	Slippery, transparent film
Color	Visual	-	Colorless
Operating temperature range	-	°C	-60 to 230°C

Above characteristics are mean values given as an information.

CAUTION

Due to the container and the presence of solvents :

- Keep away from heat, sparks and flames.
- Do not expose to heat and temperatures exceeding 50°C.
- Even when empty, do not puncture or incinerate the container.



TOTAL LUBRIFIANTS
INDUSTRY
01-11-2020
TOTAL NEVASTANE SILICONE SPRAY



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from <https://sdstotalms.total.com>