



TRANSTEC 4

Transmission Oil

KEY DATA

MANUAL GEARBOX LUBRICANT

INTERNATIONAL STANDARDS

75W-90 / 80W-90 / 85W-90 / 85W-140

✓ API GL-4

APPLICATIONS

TRANSTEC 4 is extreme-pressure lubricant for the lubrication of loaded gears for which an API GL-4 level of performance is required.

TRANSTEC 4 is suitable for all manual transmissions, transaxles, transfer boxes and steering gears in automotive and agricultural equipments which require API GL-4 level of performance.

CUSTOMER BENEFITS

- High Extreme-Pressure and antiwear performance guaranteed by a stable sulfur-phosphorous additivation.
- Good anticorrosive and antirust properties for protection of ferrous and non-ferrous components.
- Good thermal stability and anti-foaming properties.

CHARACTERISTICS*

Test	Unit	Method	Grade SAE			
			75W-90	80W-90	85W-90	85W-140
Density 15°C	kg/m ³	DIN 51757 D	866	895	909	904
Viscosity at 40 °C	mm²/s	ASTM D445	101	140	191	338
Viscosity at 100 °C	mm²/s	ASTM D445	15	14.4	17.6	25.3
Viscosity index	-	ASTM D2270	157	101	99	97
Flash point Cleveland	°C	ASTM D92	190	216	232	244
Pour point	°C	ASTM D97	-51	-27	-15	-12

^{*} The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

